



SUPERSHINE LAUNDRY SYSTEMS PVT. LTD.

Corporate & Read. Office: 205, 2nd Floor, Vipul Square, 'B' Block Sushant Lok-1,
Gurgaon - 122002 (Haryana) Phone: +91-124-4807600

E-mail: corporate@supershine.in, info@supershine.in Website: www.supershine.in

BARRIER WASHER Detailed Technical Specification

CAPACITY	120 KG
MODEL	SBW - 120
MAKE	SUPERSHINE

OVERALL DIMENSION (APPROX)

Width	Depth	Height
2100 mm	1448 mm	2035 mm

MODEL		SBW-120
CONTROL		TOUCH
CAPACITY	KG	120
CYLINDER DIAMETER	MM	1065
CYLINDER DEPTH	MM	1268
VOLUME	LITER	1129
DOOR CENTER TO FLOOR	MM	1322
COLD WATER INLET	INCH	1.5
HOT WATER INLET	INCH	1.5
STEAM INLET	INCH	1
DOSING INLET	INCH	3/4
COMPRESSED AIR INLET*	MM	8
DRAIN	MM	125
MOTOR POWER	KW	11
THREE-PHASE HEATING POWER	KW	45
MAX. EXTRACT SPEED	RPM	650
G-FORCE		250
VOLTAGE		380V/50HZ/60HZ/3PH
NET WEIGHT	KG	2360



Features:

1. Clean unloading side is separated from soiled loading side
2. Softmount with air bags, springs, and shock absorbers.
3. Stainless steel drum, tub, and door,
4. Stainless steel panels
5. Permanently lubricated bearings
6. Intelligent electronic balancing system
7. Automatic positioning of the inner drum
8. Standard configuration includes 5 chemical compartments and 5 hoses for dosing pumps.
9. Mechanical and electronic double door locks
10. Heavy duty pneumatic water valves, drain valves and steam valves

COMPRESSED AIR INLET ONLY APPLIED TO STEAM HEATED MODELS.