

GOLIATH

GENERATORI
DI VAPORE



WWW.PONY.EU



PONY
FINISHING FIRST

GE - 25



**GOLIATH COMBI
50 - 65 - 90**



**GOLIATH 50 - 65 - 90
CON SERBATOIO**



**GOLIATH 50 - 65 - 90
SENZA SERBATOIO**





GOLIATH Electric steam generators, with electronic water level controls, designed and built for an easy and quick installation. All components are easily accessible allowing simple, straightforward routine maintenance. These steam generators are built with high grade materials and conform to PED European Standards. GOLIATH steam generators are available in the following versions:

- **BASIC:** recommended for 8 - 10 hours / day of operation
- **DE LUXE:** recommended for 14 - 16 hours / day of operation
- **HEAVY DUTY:** recommended for 24 hours / day of operation.

The GOLIATH 65 and 90 models are perfect to obtain optimal performance from a Shirt finisher, a Collar & Cuff Press and for our LAV PRESS Series with polished head.

The ENERGY SAVER device is built with an upgraded pump and solenoid valve, and with a special tank to supply hot water back to the boiler up to 85°C, allowing significant energy savings. The Kit Combi allows two similar steam generators to be mounted on top of each other, complete with feeding tank, thereby doubling its power and also its hourly steam production. For models, powers and versions, see the corresponding chart.

Available extras:

- Feeding tank for water supply and condensate return, completely built in stainless steel
- Casters with support.

Technical Data	GOLIATH 25	GOLIATH 50	GOLIATH 65 - 90
Power	400/3+N/50 • 230V/3/60 Hz*		
Pump motor	0,5 kW		
Water feeding	Inner rubber tube Ø 13 mm • Ø 0,5 in		
Steam drawing	1/2"	1/2"	1/2"
Boiler drain	1/2"		
Boiler capacity	20 lt	30 lt	55 lt
Dimensions	650 x 410 x 700mm 25,5 x 16 x 27,5in	640 x 620 x 825 mm • 25 x 24,5 x 32,5 in	
Encumb. with tank	650 x 410 x 1250 mm 25,5 x 16 x 49 in	640 x 620 x 1270 mm • 25 x 24,5 x 50 in	
Encumb. COMBI	-	640 x 620 x 2100 mm • 25x 24,5 x 82,5 in	
Gross weight	110 kg • 242,5 Lbs	205 kg • 451,9 Lbs	170 kg • 375 Lbs
Gross weight with tank	145 kg • 319,6 Lbs	210 kg • 463 Lbs	215 kg • 474 Lbs
Gross weight COMBI	-	400 kg • 882 Lbs	410 kg • 904 Lbs
Package dimensions	740 x 750 x 850 mm • 29,1 x 29,5 x 33,4 in	840 x 800 x 900 mm • 33 x 31,4 x 35,11 in	
Package dimensions with tank	740 x 750 x 1380 mm • 29,1 x 29,5 x 54,3 in	840 x 800 x 1500 mm • 33 x 31,4 x 59 in	
Package dimensions COMBI	-	840 x 800 x 230 mm • 33 x 31,5 x 90,5 in	

*Other voltages by request.

For manufacturing necessities the above-mentioned specifications are not binding.

Model	Power (kW) - DHP	Steam production kg/h - Lbs/h	Steam working pressure	Kit Combi
Goliath 25	10-1 / 12-1,2 / 15-1,5 / 18-1,8	13-28 / 16-35 / 20-44 / 25-55	5 bar • 72,5 psi	
Goliath 50	24-2,4 / 26-2,6 / 28-2,8 30-3 / 33-3,3 / 36-3,6	33-72 / 36-79 / 38-83 41-90 / 45-99 / 49-108	5 bar • 72,5 psi	●
Goliath 65	30-3 / 36-3,6 / 42-4,2 / 48-4,8	41-90 / 49-108 57-125 / 65-143	7 bar • 101,5 psi	●
Goliath 90	54-5,4 / 60-6 / 66-6,6	74-163 / 82-180 / 90-198	7 bar • 101,5 psi	●

Twin heating elements for Goliath 25, available upon request. The generators 50 - 65 - 90 are built with twin heating elements as a standard.