



SUPERSHINE LAUNDRY SYSTEMS PVT. LTD.

Corporate & Read. Office: 205, 2nd Floor, Vipul Square, 'B' Block Sushant Lok-1,
Gurgaon - 122002 (Haryana) Phone: +91-124-4807600

E-mail: corporate@supershine.in, info@supershine.in Website: www.supershine.in

BARRIER WASHER Detailed Technical Specification

CAPACITY	60 KG
MODEL	SBW - 60
MAKE	SUPERSHINE

OVERALL DIMENSION (APPROX)

Width	Depth	Height
1592 mm	1448 mm	2035 mm

MODEL		SBW-60
SBW-60 CONTROL		TOUCH
CAPACITY	KG	60
CYLINDER DIAMETER	MM	1065
CYLINDER DEPTH	MM	760
VOLUME	LITER	677
DOOR CENTER TO FLOOR	MM	1322
COLD WATER INLET	INCH	1.5
HOT WATER INLET	INCH	1.5
STEAM INLET	INCH	1
DOSING INLET	INCH	3/4
COMPRESSED AIR INLET*	MM	8
DRAIN	MM	125
MOTOR POWER	KW	7.5
THREE-PHASE HEATING POWER	KW	30
MAX. EXTRACT SPEED	RPM	650
G-FORCE		250
VOLTAGE		380V/50HZ/60HZ/3PH
NET WEIGHT	KG	2110



Features:

1. Clean unloading side is separated from soiled loading side
2. Softmount with air bags, springs, and shock absorbers.
3. Stainless steel drum, tub, and door,
4. Stainless steel panels
5. Permanently lubricated bearings
6. Intelligent electronic balancing system
7. Automatic positioning of the inner drum
8. Standard configuration includes 5 chemical compartments and 5 hoses for dosing pumps.
9. Mechanical and electronic double door locks
10. Heavy duty pneumatic water valves, drain valves and steam valves

COMPRESSED AIR INLET ONLY APPLIED TO STEAM HEATED MODELS.